

AC-DC Selector Guide

3-10 Watts	15-30 Watts	40-50 Watts	60-80 Watts	100-125 Watts	130-175 Watts	180-225 Watts	250-300 Watts	350-400 Watts	500-750 Watts	800-5000 Watts	Configurable
VCE03 • 3 Watts • 1.60" x 0.75" x 0.75" • Class II • PCB Mount • 60335 Approvals	ECL15 • 15 Watts • 2.44" x 1.21" x 0.95" • Single & Multi Outputs • PCB & Chassis Mount • Class II	ECF40 • 40 Watts • 3.00" x 1.50" x 1.10" • Single Output • High Efficiency • Convection-cooled	ECS60 • 60 Watts • 3.00" x 2.00" x 1.05" • Low Leakage Current • <0.5W Standby Power • Class I & II	ECS100 • 100 Watts • 4.00" x 2.00" x 1.25" • Low Profile • <0.5W Standby Power • Class I & II	ECP130 • 130 Watts • 3.00" x 2.00" x 1.10" • 100W Convection-cooled • Up to 95% Efficiency • Low Profile	ECP180 • 180 Watts • 4.00" x 2.00" x 1.00" • Single Output • 120W Convection-cooled • Up to 95% Efficiency	CHD250 • 250 Watts • 5.00" x 3.00" x 1.43" • Medical BF Compliant • Convection-cooled • Fan Cover Options • 5V/0.5A Standby (optional)	GCS350 • 350 Watts • 5.00" x 3.00" x 1.42" • 200W Convection-cooled • Fan Cover Options • Remote On/Off	GCU500 • 500 Watts • 6.50" x 3.30" x 1.55" • 250W Convection-cooled • 5V/0.2A Standby • Class B Emissions	HDS800-3000 • 800 - 3000 Watts • High Power Density • Controls and Alarms • Programmable Voltage • Programmable Current	nanoflex • 850 - 1200 Watts • Low 1U Profile • Programmable Voltage • Programmable Current • I ² C Interface
ECE05 • 5 Watts • 1.00" x 1.00" x 0.60" • Class II • Encapsulated PCB Mount • Open Frame	EML15 • 15 Watts • 2.44" x 1.21" x 0.95" • Single Output • PCB & Chassis Mount • Class II	ECE40 • 40 Watts • 3.10" x 1.50" x 1.10" • Class II • PCB & Chassis Mount • DIN Rail Option	ECP60 • 60 Watts • 4.00" x 2.00" x 1.20" • Single & Multi Outputs • Low Profile • Peak Load Capacity	VCS100 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Low Cost	ECS130 • 130 Watts • 4.00" x 2.00" x 1.25" • Class I & II • High Efficiency • 100W Convection-cooled	GCS180 • 180 Watts • 5.00" x 3.00" x 1.42" • Class I & II • Remote On/Off Option • 150W Convection-cooled	CCM250 • 250 Watts • 6.00" x 4.00" x 1.50" • Single Output • Convection-cooled • Up to 95% Efficiency	SHP350 • 350 Watts • 7.06" x 3.60" x 2.10" • Single Output • Remote On/Off • 5V/0.5A Standby	GSP500 • 500 Watts • 6.00" x 4.00" x 1.65" • <0.5W Standby Power • Remote On/Off • 5V/2A Standby	MHP1000/SHP1000 • 1000 Watts • 9.55" x 5.90" x 2.40" • Single Output • Remote On/Off • 1200W High Line	flexPower X & XM4,5&7 • 400 - 900 Watts • 10.00" x 5.00" x 2.50" • 1 - 12 Outputs • SEMI F47 Compliant • Fan Control Option
VCE05 • 5 Watts • 1.30" x 1.10" x 0.75" • PCB Mount • Class II • Low Cost	ECE20 • 20 Watts • 2.06" x 1.07" x 0.91" • Single Output • PCB Mount • Encapsulated	ECP40 • 40 Watts • 3.00/3.50" x 2.00" x 0.90" • Single/Multi Outputs • Class I • Low Profile	ECE60 • 60 Watts • 3.60" x 1.50" x 1.10" • Class II • PCB & Chassis Mount • DIN Rail Option	ASB110 • 110 Watts • Full Brick Package • Medical BF Compliant • 4.00" x 2.00" x 0.99" • Class I & II • 100W Convection-cooled	EPL150 • 150 Watts • Medical BF Compliant • 4.24" x 2.47" x 1.16" • Class I & II • 100W Convection-cooled	UCP180 • 180 Watts • Medical BF Compliant • 4.24" x 2.47" x 1.16" • 120W Convection-cooled • 12V Fan Output	CMP250 • 250 Watts, 500W Peak • Medical BF Compliant • 7.50" x 4.00" x 1.57" • 250W Convection-cooled • 5V/1.5A Standby	SMP350 • 350 Watts • 7.00" x 3.60" x 1.70" • Single Output • Low Leakage Current • High Efficiency	LCL500 • 500 Watts • 9.84" x 5.00" x 2.08" • Single Output • Internal Fan • Low Cost	GFR1K5 • 1500 Watts • 11.80" x 4.00" x 1.70" • 1U Hot Swap • I ² C Interface • Current Share & Signals	flexPower X & XM9 • 900 - 1100 Watts • 10.00" x 6.00" x 2.50" • 1 - 12 Outputs • SEMI F47 Compliant • Fan Control Option
EME05 • 5 Watts • 1.50" x 1.00" x 0.60" • Class II • Encapsulated PCB Mount • Open Frame	ECS25 • 25 Watts • 3.00" x 2.00" x 0.95" • Single Output • <0.3W Standby Power • Class I & II	FCS40 • 40 Watts • 3.00" x 2.00" x 1.03" • Single Output • <0.15W Standby Power • Class I & II	FCS60 • 60 Watts • 4.00" x 2.00" x 1.04" • Single Output • <0.15W Standby Power • Class I & II	ECP150 • 150 Watts • 4.00" x 2.00" x 1.26" • Single Output • 100W Convection-cooled • Up to 92% Efficiency	CCB200 • 200 Watts • 5.00" x 3.00" x 1.43" • Full Power to +70 °C • Convection-cooled • Up to 95% Efficiency	GCS250 • 250 Watts • 5.00" x 3.00" x 1.42" • Class I & II • Remote On/Off Option • 180W Convection-cooled	FCM400 • 400 Watts • 6.00" x 4.00" x 1.93" • Single Output • Low Noise Fan • 5V/0.5A Standby	FCM400 • 400 Watts • 8.43" x 4.02" x 1.69" • Single Output • Baseplate-cooled • Industrial & MIL-STD	CCH600 • 600 Watts • 8.43" x 4.02" x 1.69" • Single Output • Baseplate-cooled • Industrial & MIL-STD	HPU1K5/HPD1K5 • 1500 Watts • 12.75" x 4.00" x 1.70" • Low Profile • Current Share • Programmable Voltage	flexPower X & XM10 • 1000 - 1200 Watts • 10.00" x 7.00" x 2.50" • 1 - 14 Outputs • SEMI F47 Compliant • Fan Control Option
ECL05/10 • 5/10 Watts • 2.00" x 1.00" x 0.90" • Single Output • PCB & Chassis Mount • Class II	ECL25/30 • 25/30 Watts • 2.96" x 1.36" x 1.05" • Single & Multi Outputs • PCB & Chassis Mount • Class II	ECS45 • 45 Watts • 3.00" x 2.00" x 1.05" • Low Leakage Current • <0.3W Standby Power • Class I & II	ECS65 • 65 Watts • 4.00" x 2.00" x 1.05" • Class I & II • <0.5W Standby Power • Low Leakage Current	GCS150 • 150 Watts • 5.00" x 3.00" x 1.42" • High Efficiency • Class I & II • 110W Convection-cooled	EPL225 • 225 Watts • 4.00" x 2.00" x 1.26" • 150W Convection-cooled • 12V Fan Output • Up to 95% Efficiency	EPL225-A • 225 Watts • 5.00" x 3.00" x 1.00" • Single Output • 12V Fan Output • 150W Convection-cooled	GCS265 • 265 Watts • 5.00" x 3.50" x 1.43" • 180W Convection-cooled • 5V/3A Standby • Class I & II	CCL400 • 400 Watts • 7.00" x 3.95" x 1.57" • Convection-cooled • 94% Efficiency • 5V/0.5A Standby	MHP650/SHP650 • 650 Watts • 9.18" x 4.00" x 2.50" • Single Output • Remote On/Off • Mechanical Options	HDL3000 • 3000 Watts • 12.48" x 6.69" x 2.50" • Programmable Voltage • Programmable Current • Parallel Operation	flexPower XT16 • 1600 Watts • 11.00" x 7.00" x 2.50" • 1 - 14 Outputs • 3 Phase Input • Fan Speed Control
ECE10 • 10 Watts • 1.50" x 1.00" x 0.60" • Class II • Encapsulated PCB Mount • Open Frame	EML30 • 30 Watts • 2.96" x 1.36" x 1.05" • Single Output • PCB & Chassis Mount • Class II	VCS50 • 50 Watts • 4.35" x 3.07" x 1.38" • Single Output • Convection-cooled • Low Cost	VCS70 • 70 Watts • 5.12" x 3.88" x 1.61" • Single Output • Convection-cooled • Low Cost	LCL150 • 150 Watts • 7.55" x 3.74" x 1.97" • Single Output • Convection-cooled • Low Cost	ECP225-A • 225 Watts • 5.00" x 3.00" x 1.00" • Single Output • 12V Fan Output • 150W Convection-cooled	LCL300 • 300 Watts • 8.07" x 4.33" x 1.97" • Single Output • Remote On/Off • Low Cost	CCH400 • 400 Watts • 8.43" x 4.02" x 1.69" • Single Output • Baseplate-cooled • Industrial & MIL-STD	HHP650 • 650 Watts • 9.99" x 4.20" x 2.50" • Conformal Coating • SEMI F47 Compliant • 6kV Surge Rating	HPD4K5 • 4500 Watts • 15.00" x 4.25" x 6.50" • Programmable Voltage • Controls & Signals • SEMI F47 Compliant	flexPower X & XM15 • 1500 - 2500 Watts • 11.00" x 5.00" x 5.00" • 1 - 20 Outputs • SEMI F47 Compliant • Fan Control Option	
VCE10 • 10 Watts • 2.00" x 1.15" x 0.90" • Class II • PCB Mount • 60335 Approvals	ECE80 • 80 Watts • 3.60" x 1.80" x 1.10" • Class II • PCB & Chassis Mount • DIN Rail Option	RCL175 • 175 Watts • 5.50" x 3.70" x 1.28" • Single & Multi Outputs • Class I & II • Mechanical Options	UCP225 • 225 Watts • 5.00" x 3.12" x 1.18" • 5V/2A Standby • 12V Fan Output • 150W Convection-cooled	GSP750 • 750 Watts • 13.00" x 4.00" x 1.65" • Up to 900W Peak Power • Remote On/Off • 5V/3A Standby	HPT5K0 • 5000 Watts • 13.00" x 5.00" x 5.00" • Programmable Voltage • Programmable Current • Parallel Up To 5 Units	flexPower XT15 & 30 • 1500 & 3000 Watts • 15: 11.00" x 7.00" x 2.50" • 30: 12.50" x 5.00" x 5.00" • 3 Phase Input • 1 - 7 & 1 - 10 Outputs					

= Green Product
 = Medical Version Available

External/DIN Rail Selector Guide

5-12 Watts	18 Watts	24-30 Watts	36-45 Watts	50-65 Watts	65-85 Watts	85-90 Watts	100-120 Watts	150-180 Watts	220-250 Watts	DIN Rail	DIN Rail 3 Phase		
VER05 • 5 Watts • Energy Efficiency Level VI • 2.16" x 1.45" x 1.69" • Changeable Input Plugs • LPS Approved	ACM18 • 18 Watts • Level VI & CoC Tier 2 • 3.46" x 1.18" x 1.95" • Optional White Case • 2 x MOPP	ACM24 • 24 Watts • Level VI & CoC Tier 2 • 3.46" x 1.18" x 2.24" • Optional White Case • 2 x MOPP	ACM36 • 36 Watts • Level VI & CoC Tier 2 • 3.81" x 1.30" x 2.34" • Optional White Case • 2 x MOPP	VEC50 • 50 Watts • Level VI & CoC Tier 2 • 4.58" x 2.06" x 1.23" • CCC Qualified • LPS Approved	ALM65 • 65 Watts • Energy Efficiency Level VI • 4.94" x 2.19" x 1.32" • Class I & II Versions • 2 x MOPP	AHM85 • 85 Watts • Energy Efficiency Level V • 5.90" x 2.52" x 1.45" • IP22 Rating • Class I & II Versions	AHM100 • 100 Watts • Energy Efficiency Level V • 6.49" x 2.52" x 1.45" • IP22 Rating • Class I & II Versions	AHM150 • 150 Watts • Energy Efficiency Level V • 7.80" x 3.15" x 1.45" • IP22 Rating • Class I & II Versions	AHE220 • 220 Watts • Energy Efficiency Level VI • 7.76" x 3.46" x 1.73" • High Power Density • <0.21 W Standby Power	DNR05-18 • 5 - 18 Watts • Up to 89% Efficiency • Full Power to +60 °C • ANSI/ISA 12.12.01 • Wide Output Range	DNR120TS • 120 Watts • Up to 89% Efficiency • Full Power to +60 °C • 3 Phase Input • ANSI/ISA 12.12.01		
VEL05 • 5 Watts • Energy Efficiency Level VI • 2.17" x 1.40" x 0.95" • Low Cost • LPS Approved	VEL18 • 18 Watts • Level VI & CoC Tier 2 • 3.54" x 1.34" x 1.87" • Low Cost • LPS Approved	VEL24 • 24 Watts • Level VI & CoC Tier 2 • 3.54" x 1.34" x 1.87" • Low Cost • LPS Approved	AKM36 • 36 Watts • Level VI & CoC Tier 2 • 4.25" x 1.97" x 1.33" • Optional White Case • 2 x MOPP	AKM65 • 65 Watts • Level VI & CoC Tier 2 • 4.92" x 2.45" x 1.34" • Optional White Case • 2 x MOPP	VEC65 • 65 Watts • Level VI & CoC Tier 2 • 4.58" x 2.06" x 1.23" • CCC Qualified • LPS Approved	AJM90 • 90 Watts • Energy Efficiency Level VI • 5.51" x 2.80" x 0.87" • Class I & II Versions • Very Low Profile	VES120 • 120 Watts • Level VI & CoC Tier 2 • 6.61" x 2.80" x 1.48" • CCC Qualified • Low Cost	VES150 • 150 Watts • Level VI & CoC Tier 2 • 6.66" x 2.79" x 1.56" • CCC Qualified • Low Cost	AHM250 • 250 Watts • Energy Efficiency Level V • 8.80" x 3.48" x 1.46" • IP22 Rating • Low Profile	DPC30-70 • 30 - 70 Watts • Up to 89% Efficiency • Screw Terminals • Ultra Slim Design • Wide Output Range	DNR240TS • 240 Watts • Up to 91% Efficiency • Full Power to +60 °C • 3 Phase Input • ANSI/ISA 12.12.01		
ACM06 • 6 Watts • Level VI & CoC Tier 2 • 2.89" x 1.67" x 1.21" • Optional White Case • 2 x MOPP	VER18 • 18 Watts • Level VI & CoC Tier 2 • 3.01" x 1.61" x 1.48" • Changeable Input Plugs • LPS Approved	VER24 • 24 Watts • Level VI & CoC Tier 2 • 3.54" x 1.69" x 1.68" • Changeable Input Plugs • LPS Approved	VEL36 • 36 Watts • Level VI & CoC Tier 2 • 3.70" x 1.38" x 1.83" • Low Cost • LPS Approved	ALM85 • 85 Watts • Level VI & CoC Tier 2 • 5.31" x 2.44" x 1.45" • IP32 Rating • 2 x MOPP	VE590 • 90 Watts • Level VI & CoC Tier 2 • 5.47" x 2.28" x 1.22" • CCC Qualified • Low Cost	ALM120 • 120 Watts • Level VI & CoC Tier 2 • 6.61" x 2.80" x 1.48" • CCC Qualified • 2 x MOPP	AHM180 • 180 Watts • Energy Efficiency Level V • 7.87" x 3.15" x 1.61" • IP22 Rating • Class I & II Versions	DSR75-240 • 75 - 240 Watts • Up to 94% Efficiency • Ultra Slim Design • 150% Peak Load • DC OK Signal	DNR480TS • 480 Watts • Up to 91% Efficiency • Full Power to +60 °C • 3 Phase Input • ANSI/ISA 12.12.01				
VEU10 • 10 Watts • Level VI & CoC Tier 2 • 1.45" x 0.86" x 2.0" • Low Cost • Class II Construction	VET18 • 18 Watts • Level VI & CoC Tier 2 • 4.21" x 1.71" x 1.22" • Low Cost • LPS Approved	VET24 • 24 Watts • Level VI & CoC Tier 2 • 4.21" x 1.71" x 1.22" • Low Cost • LPS Approved	VER36 • 36 Watts • Level VI & CoC Tier 2 • 3.72" x 1.85" x 1.71" • Low Cost • LPS Approved	<h2>Defense Selector Guide</h2>								DSR120-480 • 120 - 480 Watts • Up to 90% Efficiency • Full Power to +60 °C • ANSI/ISA 12.12.01 • Wide Output Range	DNR960TS • 960 Watts • Up to 93% Efficiency • Full Power to +60 °C • 3 Phase Input • ANSI/ISA 12.12.01
ACM12 • 12 Watts • Level VI & CoC Tier 2 • 2.99" x 1.19" x 1.91" • Optional White Case • 2 x MOPP	VET30 • 30 Watts • Level VI & CoC Tier 2 • 4.53" x 1.89" x 1.28" • Low Cost • LPS Approved	VET36 • 36 Watts • Level VI & CoC Tier 2 • 4.53" x 1.89" x 1.28" • Low Cost • LPS Approved	VEC40 • 40 Watts • Level VI & CoC Tier 2 • 4.58" x 2.06" x 1.23" • CCC Qualified • LPS Approved									MTC05 • 15.5-40 VDC Input • 1.26" x 0.76" x 0.34" • Single Output • MIL-STD-461 with filter • MIL-STD-1275 with filter	MTC35 • 10-40 VDC Input • 2.00" x 1.10" x 0.50" • Single Output • MIL-STD-461 with filter • MIL-STD-1275 with filter
VEL12 • 12 Watts • Level VI & CoC Tier 2 • 2.99" x 1.16" x 1.55" • Low Cost • LPS Approved	VET30 • 30 Watts • Level VI & CoC Tier 2 • 4.53" x 1.89" x 1.28" • Low Cost • LPS Approved	VET36 • 36 Watts • Level VI & CoC Tier 2 • 4.53" x 1.89" x 1.28" • Low Cost • LPS Approved	VEC40 • 40 Watts • Level VI & CoC Tier 2 • 4.58" x 2.06" x 1.23" • CCC Qualified • LPS Approved	MTC15 • 15.5-40 VDC Input • 1.57" x 1.02" x 0.38" • Single & Dual Output • MIL-STD-461 with filter • MIL-STD-1275 with filter	MTF50 • MIL-STD Filter • 10-50 VDC Input • 1.57" x 1.02" x 0.5" • Single & Dual Output • MIL-STD-461 with filter • MIL-STD-1275 with filter	MTC75 • 10-40 VDC Input • 2.28" x 1.45" x 0.50" • Single Output • MIL-STD-461 with filter • MIL-STD-1275 with filter	DSF100 • MIL-STD Filter • 1.37" x 1.25" x 0.51" • DEF-STAN 59-411 • MIL-STD-461 • MIL-STD-1275	DSF226 • MIL-STD Filter • 2.41" x 1.45" x 0.75" • DEF-STAN 59-411 • MIL-STD-461 • MIL-STD-1275	DSF500 • MIL-STD Filter • 2.28" x 2.28" x 0.75" • DEF-STAN 59-411 • MIL-STD-461 • MIL-STD-1275				
VER12 • 12 Watts • Level VI & CoC Tier 2 • 3.01" x 1.61" x 1.48" • Changeable Input Plugs • LPS Approved	VET30 • 30 Watts • Level VI & CoC Tier 2 • 4.53" x 1.89" x 1.28" • Low Cost • LPS Approved	VET36 • 36 Watts • Level VI & CoC Tier 2 • 4.53" x 1.89" x 1.28" • Low Cost • LPS Approved	AKM45 • 45 Watts • Level VI & CoC Tier 2 • 4.82" x 2.02" x 1.24" • Optional White Case • 2 x MOPP	MTC30 • 15.5-40 VDC Input • 1.57" x 1.02" x 0.50" • Single & Dual Output • MIL-STD-461 with filter • MIL-STD-1275 with filter	MTC50 • 10-40 VDC Input • 2.28" x 1.45" x 0.50" • Single Output • MIL-STD-461 with filter • MIL-STD-1275 with filter	MCS100 • 90-264 VAC Input • 6.30" x 2.95" x 1.57" • Single Output • MIL-STD-461 • 85% Efficiency	MTC150 • 10-40 VDC Input • 2.40" x 2.28" x 0.50" • Single & Dual Output • MIL-STD-461 with filter • MIL-STD-1275 with filter	MCC400 • 1-4 Configurable O/P's • 7.28" x 6.49" x 1.08" • 400 W Regulated O/P's • MIL-STD-1275 • MIL-STD-461	MCC600 • 1-4 Configurable O/P's • 7.28" x 6.49" x 1.08" • 400 W Regulated O/P's • MIL-STD-1275 • MIL-STD-461				

= Green Product
 = Medical Version Available

For full specifications visit:
www.xppower.com